



PRECISION QUINCY

Pre-Engineered Genset Enclosures

SAE Stand-By Power Packages

Precision Quincy Industries specializes in preengineered UL FTPP Classified, sound attenuated enclosure models. Designed to reduce the source noise(s) by 30 dB(A) @ 23' (in a free-field environment); constructed from 5052 aluminum or 14 gauge galvalume roll-formed and welded frame.

Performance proven VHB adhesive bonds the aluminum or galvalume skin to the frame to offer a smooth exterior finish, free of rivets, bolts or other hardware. Proven through third party engineering evaluation, our enclosures are rated for 120 MPH wind load, 50 lbs./square inch roof load and 200 lbs./square inch floor load. Each model can be incorporated with a 24 hour or 48 hour run time, UL142 sub base diesel fuel supply tank. Flexibility in our design allows room for additional non-standard components to be specified.

Pre-Engineered Enclosure Features

- Sound reduction of 30 dB(A) @ 23'
- Critical grade insulated silencer
- Insulated access doors, 3-point latch and safety holdbacks
- 12" Sub-frame (available on the PQ-1000)

Pre-Engineered Enclosure Specs

- Wind Load – 120 MPH
- Roof Load – 50 pounds/ SF
- Floor load – 200 pounds/ SF

Pre-Engineered Enclosure Sizes

| Model | Length | Width | Height |
|---------|--------|-------|--------|
| PQ-500 | 300" | 96" | 120" |
| PQ-700 | 324" | 114" | 126" |
| PQ-1000 | 372" | 114" | 150" |



Contact us today

4600 N. Mason Montgomery Road | Mason, OH 45040
513-923-5900 | sales@PQInd.com

www.PQInd.com

A Division of The Armor Group, Inc.






Pre-Engineered Enclosure Packages

Pre-Engineered Electrical Options Can Also Be Purchased Separately

- Duplex GFCI outlets
- Weatherproof outlet box and cover
- E-stop switch w/glass break
- Dual lamp, battery back-up emergency lights
- Rotating beacon
- 3 alarm panel
- 4 alarm panel
- 5 alarm panel
- 100A fused disconnect switch
- Transformer 30 kVA 480/208 30
- Square-D load center, QO124M 150 120/240V, 150A, 10
- Additional load centers available
- Motorized and gravity dampers
- Seismic isolators



Pre-Engineered Electrical Options

Package A - Junction Box

- 12" x 10" x 6" panel and terminal box

Package B – 10 or 30 Main C/B Options

- 240/120V, 10, 100A main circuit breaker panelboard
- 240/120V, 30 100A main circuit breaker panelboard
- Incandescent vapor tight lights
- 3-way light switch
- GFCI duplex outlet

Package C – 10 or 30 Main C/B Options

Same as Package B, plus:

- 5kW space heater
- 24VDC Light (160W) clear lens
- Timer switch wind-up (0-60 Min)
- E-stop switch w/break glass.
- 12" thermostatically controlled exhaust fan
- LED wall pack security light W D2D
- Motorized dampers
- Gravity dampers

Sub-Base Fuel Tanks

Pre Engineered UL Listed Sub-Base Fuel Tank Features

- UL142 listed
- 2" normal vent extended 12' above grade
- 1 year warranty

Additional Options

- Spill containment w/lockable lid
- 2" white lettering on fuel tank



Pre-Engineered Enclosure Sizes

| Capacity | Length | Width | Height | Compatatible with |
|----------|--------|-------|--------|-------------------|
| 24 Hour | 376" | 96" | 16" | PQ-500 |
| 48 Hour | 376" | 96" | 27" | PQ-500 |
| 24 Hour | 422" | 114" | 15" | PQ-700 |
| 48 Hour | 422" | 114" | 25" | PQ-700 |
| 24 Hour | 422" | 114" | 23" | PQ-1000 |
| 48 Hour | 422" | 114" | 40" | PQ-1000 |



Contact us today

4600 N. Mason Montgomery Road | Mason, OH 45040
513-923-5900 | sales@PQInd.com

www.PQInd.com

